


Documentation

Check Valves PN 16 ***- Type RUCK ... -***



1. Direction

1. Direction	1
2. Description	1
3. Technical specifications	1
4. Dimensions	1

2. Description

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems. It can be installed in any position: vertical, horizontal, oblique.

3. Technical specifications

Body: brass
Plate: nylon
Seal: NBR
Spring: stainless steel
Minimum and maximum working temperatures: -20°C, 100°C
Threads: ISO228
 (equivalent to DIN259 and BS2779)

4. Dimensions

Typ	G	L	D	CH	PN	Öffnungsdruck
RUCK 14	G 1/4"	45,0	---	SW 22	16	0,10 bar
RUCK 38	G 3/8"	46,5	34,5	SW 21	12	0,02 bar
RUCK 12	G 1/2"	47,0	34,5	SW 26	12	0,02 bar
RUCK 34	G 3/4"	53,0	42,0	SW 32	12	0,02 bar
RUCK 10	G 1"	60,5	47,5	SW 39	12	0,02 bar
RUCK 114	G 1 1/4"	66,5	59,5	SW 47	10	0,02 bar
RUCK 112	G 1 1/2"	74,0	70,5	SW 55	10	0,02 bar
RUCK 20	G 2"	80,0	86,0	SW 66	10	0,02 bar
RUCK 212	G 2 1/2"	98,0	102,0	SW 83	8	0,02 bar
RUCK 30	G 3"	103,0	125,0	SW 96	8	0,02 bar
RUCK 40	G 4"	118,5	154,0	SW 123	8	0,02 bar

